

TONDO E RETE PER EDILIZIA

- TONDO AD ADERENZA MIGLIORATA
- RETE AD ADERENZA MIGLIORATA

TONDO AD ADERENZA MIGLIORATA



diametro	Peso	Note
mm	kg/m	(Tolleranza peso %)
6.00	0.222	10.00
7.00	0.305	9.00
8.00	0.395	8.00
9.00	0.500	8.00
10.00	0.616	8.00
11.00	0.745	8.00
12.00	0.888	8.00
14.00	1.210	6.00
16.00	1.580	6.00
18.00	2.000	6.00
20.00	2.465	6.00
22.00	2.982	5.00
24.00	3.558	5.00
26.00	4.172	5.00
28.00	4.853	5.00
30.00	5.546	5.00
32.00	6.315	5.00
36.00	7.990	5.00
40.00	9.870	5.00

RETE ELETTROSALDATA AD ADERENZA MIGLIORATA

Maglia	pannello		diametro filo	Peso pannello
	mm	mm		
100x100	2000	3000	4.00	11.88
100x100	2250	4000	4.00	18.02
150x150	2000	3000	4.00	8.11
150x150	2250	4000	4.00	11.95
200x200	2000	3000	4.00	5.94
200x200	2250	4000	4.00	9.20
100x100	2000	3000	5.00	18.48
100x100	2000	5000	5.00	30.80
150x150	2000	3000	5.00	12.60
150x150	2000	5000	5.00	21.00
200x200	2000	3000	5.00	9.24
200x200	2250	4000	5.00	14.31
200x200	2470	6000	5.00	23.43
100x100	2000	3000	6.00	26.64
100x100	2000	5000	6.00	44.40
100x100	2400	4000	6.00	42.62
150x150	2000	3000	6.00	18.12
150x150	2000	5000	6.00	30.20
200x200	2000	3000	6.00	13.32
200x200	2250	4000	6.00	20.66
100x100	2400	4000	8.00	75.65
150x150	2000	3000	8.00	32.22
150x150	2000	5000	8.00	53.70
200x200	2000	3000	8.00	23.64
200x200	2250	4000	8.00	36.74
200x200	2250	4000	10.00	57.38
200x200	2250	4000	12.00	82.77